

SIDE SLINGER

Available in two model sizes: 800 & 1,000



Designed to handle a wide range of manure from solid to slurry, the Hi-Spec Side Slinger is one of the leading side spreaders on the market today. Once in operation it unloads fast and gives an even, consistent spread pattern.

FEATURES:

- A strong chassis frame - giving maximum support, durability and strength to the main drum.
- Heavy duty flails and a 12mm chain case hardened for longer life.
- Chain brackets mounted on the rotor in four banks to facilitate easy driving and smoother running.
- 168mm diameter heavy duty flail rotor.
- Both bearings are mounted away from the drum for longer life.
- All machines are finished with two coats of paint, anti-corrosive primer and an enamel finish, giving a high quality long lasting finish.

HiSPEC

Built to last

Simple, reliable
& Strong

HI-SPEC ENGINEERING LTD.

Station Road
Bagenalstown
Co. Carlow, Ireland
Tel: (059) 972 19 29 / 972 19 92
Fax: (059) 972 19 80
from UK: (00 353 59)
Hi-Spec website address
www.hispec.net
E-mail: sales@hispec.net

Hi-Spec Side Slinger



SPECIFICATIONS

Model	800	1,000
Loading Height:	1500mm (4'11")	1680mm (5'6")
Overall Length:	4725mm (15'6")	5430mm (17'10")
Overall Height:	2490mm (8'2")	2540mm (8'4")
Overall Width:	2500mm (8'3")	2550mm (8'4")
Wheels:	15 x 22.5	BN3
Driver Sprocket:	14 tooth standard, other sizes available	14 tooth standard, other sizes available
Driven Sprocket:	33 tooth, 31mm (1 1/4") pitch	33 tooth, 31mm (1 1/4") pitch
Rotor Speed:	229 revs/min.	229 revs/min.
Hitch:	Ring hitch and parking stand	Ring hitch and parking stand
Brakes:	Hydraulically operated	Hydraulically operated
Lights:	Standard	Standard
Lid:	Hydraulically operated	Hydraulically operated
H.P. Requirement:	75 h.p.	90 h.p.

BUILT AS THE NAME SUGGESTS